

STATIONARY DOCK SHELTER

Model	BGDSHS (US)	BG400 (CAN)
Fits Standard Door Size	10.5' x 10.5' (3.2 x 3.2 m)	
Seals Trailer Heights	12' - 13.5' (3.7 - 4.1 m) - on typical 4' (1.2 m) dock height	
Components	One (1) head curtain, two (2) side curtains, two (2) side frames, one (1) head frame, two (2) steel guards, three (3) trim angles, two (2) bottom draft pads	
Frame	Pressure-treated lumber with translucent sheeting. Protected by steel guards. Peaked in the center to allow for drainage. Exterior front frame edges have 1.5" x 2.5" (40 x 65 mm) galvanized trim angle	
Head Curtain	138" (3,505 mm) wide with 36" (914 mm) drop with 20" x 10" (508 x 254 mm) 40oz. protective flaps/pleats at corner impact area	
Cover Material	Polyester base using 40oz. premium grade vinyl (recommended)	
Side Curtains	24" wide x 120" high (610 x 3,048 mm) with 4" x 24" (102 x 610 mm) heat sealed yellow guide stripes	
Mounting Hardware	Galvanized	
Warranty	Subject to standard limitations on liability. See www.bluegiant.com/support/product-warranty for more information	

OPTIONAL FEATURES

- Curtain: 22/50oz. premium grade vinyl or ArmorShield™ or 40oz. Thermalon
- Pleat/Flap: 22/50oz. premium grade vinyl or 40oz. Thermalon
- Reflective guides
- Additional projection of 30", 36", or 48" (762, 914, 1,219 mm)
- Gussets in head curtains
- Additional drop in head curtain (per inch)
- Additional width in side curtains (per inch)

- Double layer of fabric on bottom 24" (610 mm) of side curtain 22/40/50oz. vinyl or ArmorShield™ or 40oz. Thermalon
- Reinforced edges on side pads
- Additional header width
- Additional side frame height
- Full height yellow guide stripe
- Painted steel frame
- Galvanized steel frame with galvanized sheeting



Corporate 410 Admiral Blvd Mississauga, ON, Canada L5T 2N6 t 905.457.3900 f 905.457.2313 USA 6350 Burnt Poplar Road Greensboro, NC 27409 www.bluegiant.com AUTHORIZED DEALER

Blue Giant offers a full line of dock levelers, dock safety equipment, seals and shelters, accessories, ergonomic and scissor lift equipment and industrial trucks. Concurrent with our continuing product improvement program, specifications are subject to change without notice. Please contact Blue Giant for latest information. Some features illustrated may be optional in certain market areas.